RANGE OF TONE CONTROLS

Treble: +10 to -10 dB at 10 KHz.

Bass: +12 to -15 dB at 50 Hz.

Volume control at mid-position.

INDIVIDUAL MODEL DETAILS

	11-124	11-125
Transistors	15	17
Diodes	5	5
Command Module	Console	Console
Command Module Lid	Tinted Acrylic	Tinted Acrylic
Record Changer	BSR MA70	Garrard SL65
Cartridge	C1 Ceramic	Shure Dynetic M44-7
Stylus	ST4 Diamond	Shure N44-7 diamond
Speaker Modules (each)	(10" - 10 P1X 8 ohms Magnavox	(12" – 12 PEG 8 ohms Rola
	(5" – HF5S1C 8 ohms Magnavox	(5" – 5 FX 8 ohms Rola

	11-126	11-127
Transistors	17	15
Diodes	5	5
Command Module	Console	Table (with stand)
Command Module Lid	Tinted Acrylic	Tinted Acrylic
Record Changer	Garrard SL65	BSR MA70
Cartridge	Shure Dynetic M44-7	C1 Ceramic
Stylus	Shure N44-7 Diamond	ST4 Diamond
Speaker Modules (each)	(15" – C15W 8 ohms Magnavox	(8" – C8MX/17 8 ohms Rola
	(2 x 5" – HF5S1C 15 ohms Magnavox	(3" – 3DX00 8 ohms Rola

DIMENSIONS

Model No.	Unit	Height	Width	Depth	Packed Weight
11-124	Command Module	26"	24½"	14¾"	168 lb.
	each Satellite Module	26"	18 "	14¾"	
11-125	Command Module	26"	24½"	14¾"	181 lb.
	each Satellite Module	26"	21¼"	14¾"	
11-126	Command Module	27"	24½"	14¾"	203 lb.
	each Satellite Module	27"	23¼"	14¾"	
11-127	Command Module	22" (with 13" legs)	25¾"	15 "	101 lb.
	each Satellite Module	20¼"	13 "	9½"	