

# High-Mu Triode— Sharp-Cutoff Pentode

## 9-PIN MINIATURE TYPE

### GENERAL DATA

#### Electrical:

Heater Characteristics and Ratings (*Design-Center Values*):

Voltage (AC or DC) . . . . .	6.3 ± 0.6	volts
Current at heater volts = 6.3 . . .	0.720	amp

Peak heater-cathode voltage

(Each unit):

Heater negative with respect to cathode . . . . . 200 max. volts

Heater positive with respect to cathode . . . . . 200 max. volts

Direct Interelectrode Capacitances:<sup>a</sup>

*Triode Unit:*

Grid to plate . . . . . 2.7  $\mu\mu\text{f}$

Grid to all other elements except plate . . . . . 4.0  $\mu\mu\text{f}$

Plate to all other elements except grid . . . . . 2.3  $\mu\mu\text{f}$

Grid to heater . . . . . 0.1 max.  $\mu\mu\text{f}$

*Pentode Unit:*

Grid No.1 to plate . . . . . 0.1 max.  $\mu\mu\text{f}$

Grid No.1 to all other elements except plate . . . . . 9.0  $\mu\mu\text{f}$

Plate to all other elements except grid No.1 . . . . . 4.5  $\mu\mu\text{f}$

Grid No.1 to heater . . . . . 0.1 max.  $\mu\mu\text{f}$

Triode plate to pentode grid No.1 . . . . . 0.01 max.  $\mu\mu\text{f}$

Triode grid to pentode grid No.1 . . . . . 0.01 max.  $\mu\mu\text{f}$

Characteristics, Class A<sub>1</sub> Amplifier:

	<i>Triode Unit</i>	<i>Pentode Unit</i>			
Plate Voltage . . . . .	200	170	200	220	volts
Grid-No.2 Voltage . . . . .	-	170	200	220	volts
Grid-No.1 Voltage . . . . .	-1.7	-2.1	-2.9	-3.4	volts
Amplification Factor . . . . .	65	-	-	-	
Mu Factor, Grid No.2 to Grid No.1 . . . . .	-	36	36	36	
Plate Resistance (Approx.) . . . . .	-	0.1	0.13	0.15	megohm
Transconductance . . . . .	4000	11000	10400	10000	$\mu\text{mhos}$
Plate Current . . . . .	3	18	18	18	ma
Grid-No.2 Current . . . . .	-	3	3	3	ma

#### Mechanical:


Operating Position . . . . .	Any
Type of Cathodes . . . . .	Coated Unipotential
Maximum Overall Length . . . . .	2-5/8"
Maximum Seated Length . . . . .	2-3/8"



# 6DX8

Length, Base Seat to Bulb Top (Excluding tip) . . . 2"  $\pm$  3/32"  
 Diameter . . . . . 0.750" to 0.875"  
 Dimensional Outline . . . . . See *General Section*  
 Bulb . . . . . T6-1/2  
 Base . . . . . Small-Button Noval 9-Pin (JEDEC No. E9-1)  
 Basing Designation for BOTTOM VIEW . . . . . 9HX

Pin 1 - Triode  
 Grid  
 Pin 2 - Triode  
 Plate  
 Pin 3 - Triode  
 Cathode  
 Pin 4 - Heater  
 Pin 5 - Heater  
 Pin 6 - Pentode  
 Plate



Pin 7 - Pentode  
 Grid No. 3,  
 Pentode  
 Cathode,  
 Internal  
 Shield  
 Pin 8 - Pentode  
 Grid No. 1  
 Pin 9 - Pentode  
 Grid No. 2

## AMPLIFIER — Class A<sub>1</sub>

### Maximum Ratings, Design-Center Values:

	Triode Unit	Pentode Unit	
PLATE SUPPLY VOLTAGE . . . . .	550 max.	550 max.	volts
PEAK PLATE VOLTAGE with maximum plate ma. = 0.1 <sup>b</sup> . . . . .	600 max.	-	volts
PLATE VOLTAGE . . . . .	300 max.	300 max.	volts
GRID-No. 2 (SCREEN-GRID) SUPPLY VOLTAGE . . . . .	-	550 max.	volts
GRID-No. 2 VOLTAGE . . . . .	-	300 max.	volts
CATHODE CURRENT . . . . .	12 max.	40 max.	ma
GRID-No. 2 INPUT . . . . .	-	1.7 max.	watts
PLATE DISSIPATION . . . . .	1 max.	4 max.	watts

### Typical Operation (Pentode Unit):

#### As video-output tube

Plate Supply Voltage . . . . .	170	200	220	volts
Series Plate Resistor . . . . .	3000	3000	3000	ohms
Grid-No. 2 Voltage . . . . .	170	200	220	volts
Grid-No. 1 Voltage . . . . .	-2	-2.8	-3.3	volts
Transconductance . . . . .	10400	10000	9700	$\mu$ mhos
Plate Current . . . . .	18	18	18	ma
Grid-No. 2 Current . . . . .	3.2	3.1	3.1	ma

### Maximum Circuit Values:

	Triode Unit	Pentode Unit	
Grid-No. 1-Circuit Resistance: For fixed-bias operation . . . . .	1 max.	1 max.	megohm
For cathode-bias operation . . . . .	3 max.	2 max.	megohms

<sup>a</sup> Without external shield.

<sup>b</sup> With duty factor = 0.18 maximum and pulse duration = 18 microseconds maximum.

