Circuit No.	Description	Tol±	Rating	Part No.
144	Speaker Input Transformer - 10,000 CT: 2 ohms Imped Code.No.K4-2			T130
145	Electrostatic Speaker			K210
146	8" dia. permag Speaker type 8M cone No.F57			K214
147	8" dia. permag Speaker type 8M cone No.F62			K215
148	Wave Change Switch			S224
149	Gramo-Radio Switch			S231
150	Mains ON - OFF Switch			S213
151	.0022MF paper condenser	20%	1000V DCW	H2223

Tuning condenser mt. bracket - front.	45/409-1
Tuning condenser mt. bracket - rear	45/409-2
Grommet (4) cond.mt.	64/30A
Bush (4) cond. mt.	95/53-1
Tuning spindle assy.	A121/789
Spindle retaining bracket	164/789
Dial drum	A104/698
Dial cord	34/754
Spring - dial cord	21/698
Wooden pulley $\frac{5}{8}$" dia. (2)	13/613
Wooden pulley $\frac{3}{4}$" dia.	17/87
Pulley mt. stud (3)	18/87
Dial reading	95/789
Dial mt.clips (2) top of dial	15/394
Dial mt. clips (5) base & side of dial.	60/754
Dial lamp socket assy. (3)	A577/30C
Indicator lamp socket assy.	A110/698
Light button - wave change switch band indicator	
AMBER	27/688
RED	27/688-1
GREEN	27/688-2
BLUE	27/688-4
WHITE	27/688-7
Speaker Silk 20"X12"	GX410
ASTOR name strip	392/81-3
Grille - gold plate	163/789
Cabinet back	167/789
Screw (6) $\frac{1}{2}$" x No.6 rd.hd. woodscrew cab back mt.	46/560-33

Aerial terminal	PM306
Clip (2) IF. trans mt.	7/670
Clip (3) B/cast band coil. mt.	6/622
9 pin valve socket (7)	279/350
Adaptor plate (7) socket	33/698
Single pin socket plate-top (2)	18/96
Single pin socket plate-bottom (2)	19/96
Contact (2) single pin socket	15/58-3
Terminal strip (3) 8 lug type 2E3E1	A628/30C
Terminal strip 7 lug type 1E3E1	A616/30C
Terminal strip (3) 4 lug type 1E2	A595/30C
Terminal strip - 4 lug type 2E1	A602/30C
Terminal strip - 2 lug type E1.	A599/30C
Terminal strip - 5 lug type E3E mains tap strip	A625/30C
Mains lead - 9 ft. twin flex and 3 pin plug	PA609
Mount bracket - mains switch	160/789
Nut (3) spindle bushes	542/250
Black Organdie 20" X 12"	G0151
Extension spindle (2) wave change and gramo/radio switch	153/789
Retaining bracket (2) ext. spindles.	166/789
Grub screw (2) 3/16" x 5/32" Whit. cup point - ext. spindles	30/560-3