

# SPECIFICATIONS

# H78

# Hitachi CS-1750 1C

# H78

PLAYBACK SYSTEM .....8-track 2-channel 4-program  
 CARTRIDGE .....Stereo 8 tracks  
 TAPE SPEED.....3 $\frac{3}{4}$  ips  
 IC (Integrated Circuit)  
 IC 1 TA2003 .....Pre Amp.  
 IC 2 TA2003 .....Pre Amp.  
 TRANSISTORS  
 TR1 2SC458 .....Driver  
 TR2 2SC1061 .....Power Amp.  
 TR3 2SC1061 .....Power Amp.  
 TR4 2SC458 .....Driver  
 TR5 2SC1061 .....Power Amp.  
 TR6 2SC1061 .....Power Amp.  
 TR7 2SC458 .....Ripple Filter  
 TR8 2SB77 .....Polarity Protector  
 DIODES  
 D1 HV-23 .....Temp. Comp.  
 D2 HV-23 .....Temp. Comp.  
 D3 HV-23 .....Temp. Comp.

D4 HV-23 .....Temp. Comp.  
 D5 VO-6A .....Plunger Protector  
 D6 IS2076 .....Polarity Protector  
 D7 IS2076 .....Polarity Protector  
 D8 HV-46 .....Volt. Stab.  
 D9 HV-46 .....Volt. Stab.  
 PROGRAM CHANGE SYSTEM---Automatic or push button system  
 FREQUENCY RANGE .....30~12,000Hz  
 AUDIO OUTPUT .....16W (max.)  
 8W (distortionless)  
 at 2-speakers, 4 ohm  
 IMPEDANCE .....4~8 ohm  
 POWER SUPPLY .....DC 12V negative ground  
 (Use car battery)  
 CURRENT COMSUMPTION .....0.5A  
 DIMENSIONS .....2 $\frac{1}{2}$ "(H) $\times$ 7 $\frac{1}{2}$ "(W) $\times$ 7 $\frac{1}{2}$ "(D)  
 (7.1 $\times$ 18 $\times$ 19cm)  
 WEIGHT .....5 lbs. 8 oz. (2.5kg)





