

# RADIO CORPORATION PTY. LTD.

DIVISION OF ELECTRONIC INDUSTRIES LTD.

126-130 GRANT STREET, SOUTH MELBOURNE, S.C.4.

## TECHNICAL BULLETIN

BULLETIN G-7
File:- Service
General (G)

Date: 28/7/47.

Page 1.

SUBJECT-Removing and Refitting the Chassis to the Cabinet-Models "MP" and "LS"

The procedure for removing and refitting the chassis to the cabinet for the Models "MP" and "LS" is detailed below with a diagram showing an enlarged view of one of the chassis mount bolts.

## MODEL "MP" PHONO/RADIO COMBINATION.

To remove the chassis:-

- 1. Withdraw the push on knobs from the switch and control spindles.
- 2. Unscrew the screws on the motor board holding the brackets which mount the tone control and change-over switches.
- 3. Lay the cabinet face downwards on a cushion placed near the top of the cabinet.
- 4. Disconnect the A.C. leads to the motor by unscrewing the terminals.
- 5. Disconnect the pickup leads from the change-over switch. The leads have phone tips which plug into small sockets on the switch contacts.
- 6. Loosen off the two front screws holding the chassis base plate and then unscrew and remove the two rear screws. This will allow the base plate to be withdrawn.
- 7. Unsolder the speaker leads soldered to the terminal strip on the chassis. Should it be required to remove the speaker unscrew the four screws in the speaker rim.
- 8. Unscrew the nuts "A" (refer diagram) on the four mount screws. The receiver chassis may now be removed from the cabinet by placing one hand on each end of the chassis and withdrawing it upwards. The chassis mount screws will retain their positions as they are held by nuts "B" embedded into the baffle board.

### To refit the chassis:-

The exact reverse procedure is adopted for refitting the chassis as for removing, make sure that all nuts are tight and all connections are secure.

#### MODEL "LS" CONSOLE

The procedure for removing and refitting the chassis to the cabinet for this model is the same as for the Model "MP" disregarding paragraphs 2, 4 and 5.

BULLETIN G-7

File: Service

General (G)

Date: 28/7/47.

Page: 2.

SUBJECT-Removing and Refitting the Chassis to the Cabinet-Models "MP" and "LS"

Diagrams



