

PHILIPS *Service* notes

SUPPLEMENTARY SHEET

MODEL MT10

NOTE: Read in conjunction with the sheet for Model MT10 (Aug. 1966).

In Model MT10, audio module UA402 has been replaced with module UA411 (yellow, brown, brown). This module draws different current to the previous module. New temperature/current table, parts lists and circuit drawing are published herewith.

CURRENT TABLE

The currents which apply with the use of module UA411 are:—

Temp. °F.	TR103/104 Current mA.	Receiver Current mA.
50	6.5	16.7
55	6.6	17.0
60	6.7	17.2
65	6.8	17.4
70	6.9	17.6
75	7.0	17.9
80	7.1	18.1
85	7.2	18.3
90	7.3	18.5
95	7.4	18.8
100	7.5	19.0
105	7.6	19.2
110	7.7	19.4
115	7.8	19.7

UA411 PARTS LISTS

CAPACITORS

electrolytic	C.426.AR/..
101	1M/40V	/G1
102	200M/10V	/D200
103	320M/6.4V	/C320
105	320M/6.4V	/C320
106	200M/10V	/D200

RESISTORS

101	120K	} ½W, 10% IRC BTS
102	330K	
103	220E	
104	15E	
105	4K7	
106	1K8	
111	680E	
107	130E, disc NTC	
	1W, 10% E.201.BC/A130E	
108	200E pre-set	
	E.086.AC/200E	
109	} 1E8 metal oxide	
110	} ¼W, 5%, E.017.BC/B1E8	

July, 1967

