

AUTO RADIO SERVICE BULLETIN.

SUBJECT:    INSTALLATION INSTRUCTIONS FOR 1939 CHEVROLET  
FACE PLATE - PART No. M10168 & REMOTE CONTROL M10167.

1. Remove the tenite top and bottom horizontal finish strips and the two chromium plated vertical finish strips from the centre of the instrument panel.
2. Strip the face plate studs of the mounting nuts and shakeproof washers. Now mount the face plate to the instrument panel so that the dial aperture, control mounting holes, and mounting studs on the plate match up with the corresponding holes in the instrument panel. Replace the plate mounting nuts and shakeproof washers on to the studs behind the instrument panel and tighten the nuts securely by means of a spanner or spintite to keep the escutcheon in position while mounting the control.
3. Strip the control of the knobs, plinth washer, tone control actuating arm, and loose mounting nuts before placing it up under the instrument panel, with the dial reading horizontally and above the control spindles. Match up the control spindles and dial in the apertures provided in instrument panel and face plate. Then take the locknuts and screw them on the screwed bush showing in each control hole. Tighten finally by means of a spanner or spintite. After this replace the tone control actuating arm, plinth washer, and control knobs, making sure that the tone control actuating arm is engaging with the slots in the large portion of the left hand side spindle, and that the small hole knob fits on the left hand shaft, and the large hole knob on the right hand shaft. Tighten the knobs dn finally by means of a grubscrew driver.