Rear Mount Stud shakeproof washer 5/16" int.	1/562-13
Indicator Light Button - ''Clear''	3/386-3
Indicator Light Button - ''Red''	3/386-2
Rubber Sleeve - foot switch connector	43/386
Contact Pin - foot switch connector	23/386
Contact Sleeve - foot switch connector	42/386
Universal Coupling - tuning spindle	53/813
Split Pin - tuning spindle	392/250
Receiver Metal Can - top section - blue duco	A123/366-2
Receiver Metal Can - top section - silver duco	A123/366-1
Receiver Metal Can - bottom section - blue duco	A114/321-3
Receiver Metal Can - bottom section - blue duco dunked corner	A115/321-2
Receiver Metal Can - bottom section - silver duco	A114/321-2
Receiver Metal Can - bottom section - silver duco dunked corner	A115/321-3

1st IF. TRANS.



2nd IF. TRANS.



ANTENNA COIL

Blue, Red or Green - Chassis
White or Yellow - Antenna

RF. COIL

Blue, Red or Green - A.V.C.
White or Yellow - Grid

OSCL. COIL

Blue, Red or Green - Osc. grid
White or Yellow - Oscl. plate

POWER TRANS.

Pri. start	- Red sleeving on heavy gauge wire.
Pri. centre tap	- Green sleeving on heavy gauge wire.
Pri. finish	- Black sleeving on heavy gauge wire.
Elect. Static Shield	- Yellow, stranded wire.
Sec. start	- Red cotton covered stranded lead.
Sec. centre tap	- Green cotton covered stranded lead.
Sec. finish	- Black cotton covered stranded lead.

Note: The antenna, RF. and oscl. coil coloured leads are shown above as having a particular coloured lead for connection to a specific point. Either coloured lead may be connected to either of the specified points for the respective coil without any detrimental effect to the receiver.