



<b>circuit;</b>	3 Speed 2 Band 7 Transistor portable Radio-Phonograph	varistor; HV-16
<b>frequency range;</b>	BC. 535 ~ 1605 K C SW 3.82 ~ 11.0 MC	diode, IN34 A × 2
<b>sensitivity;</b>	B C { 610 K C 48 D B 1000 K C 46 D B 1400 K C 46 D B S W { 4.2 MC 45 D B 6.5 MC 43 D B 10 MC 43 D B	speaker; 4" × 6" Permanent dynamic speaker
<b>output power;</b>	400 mW	turntable; Dia 6 ½"
<b>transistor;</b>	CONV 2 SA 15 or 2 N 219	pick-up; turn over LP · SP crystal pick-up
	AF. AMP 2 NB 75 or 2 N 215 × 2	speed; 33 ⅓, 45 78 r. p. m.
	IF. AMP 2 SA 14 or HJ - 62 × 2	dimension; 5 ⅛ × 9 ⅞ × 13 ⅜"
	P. AMP 2 SB 77 or 2 N 217 × 2	weight; 4.5 kg
		battery, Maxell or Flattery UM - 1 × 6 9 V

**3 SPEED 2 BAND 7 TRANSISTOR PORTABLE RADIO-PHONOGRAPH · TRP · 20**